REMARKS/ARGUMENTS

Please enter the amendment under the provisions of 37 CFR 1.1126. It is respectfully submitted that the amendment to claim 1 has not changed the substance of claim 1 as originally filed or as previously amended. The examiner objected to the use of the term "otherwise". The applicant attempted to remove that objection with the previous amendment. The applicant now again tries to remove that objection. However, the claim is the same in substance as originally filed and this amendment does not raise any new issues. Therefore, this amendment should be entered for purposes of appeal.

Further, the substantive issue still remains, and that is whether Lentz et al. grants default access to the bus to a predetermined one of the candidates. More particularly, the essential issue here is whether, in the default case when no candidate is requesting the bus, the action of "***assigning*** a priority", as in Lentz et al., is a different action than actually "***granting*** access to the bus", as claimed.

In the art, the action of granting bus access to a given candidate in the absence of a bus request by *any* of the candidates is referred to as "parking" the given candidate on the bus. The significant difference between "parked" and "non-parked" arbitration schemes is well known in the art and is described, by example, in the attached pages 9-13 and 9-14 of the MPC7450 RISC Microprocessor Family User's Manual by Motorola.

Thus, as pointed out in the applicant's previous response, the claim states that one of the candidates ***is granted*** access to the bus, *even in the absence of any bus request (the "default")*. Thus, even assuming argunendo that Lentz et al. ***assigns*** a highest priority to a candidate in the absence of any bus request, as alleged by the examiner, the applicant takes the process ***one step further*** by actually granting access to the bus to the predetermined one

of the candidates. The examiner has not pointed out where Lentz et al. describes this further granting step. The applicant again requests that the examiner point out the column and line number where Lentz et al. allegedly states that the highest priory candidate is *actually granted access to the bus in the absence of a bus request.*

In the event any additional fee is required, please charge such amount to Patent and Trademark Office Deposit Account No. 50-0845.

Respectfully submitted,

1-8-04
Date

Richard M. Sharkansky
Attorney for Applicant(s)
Reg. No.: 25,800
Daly, Crowley, & Mofford, LLP
275 Turnpike Street, Suite 101
Canton, MA 02021-2354
Telephone: (781) 401-9988, 23
Facsimile: (781) 401-9966

Q:\emc2\EMC2-081PUS(122001)\emc2-081pus response to oa mailed 10-10-03 21Oct03.doc

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.

MOTOROLA intelligence everywhere digital dna



MPC7450 RISC Microprocessor Family User's Manual

Devices Supported:
MPC7455, MPC7451, MPC7450,
MPC7445, MPC7441

HOW TO REACH US:

USA/EUROPE/LOCATIONS NOT LISTED:

Motorola Literature Distribution;
P.O. Box 5405, Denver, Colorado 80217
1-303-675-2140 or 1-800-441-2447

JAPAN:

Motorola Japan Ltd.;
SPS, Technical Information Center,
3-20-1, Minami-Azabu Minato-ku,
Tokyo 106-8573 Japan
81-3-3440-3569

ASIA/PACIFIC:

Motorola Semiconductors H.K. Ltd.;
Silicon Harbour Centre, 2 Dai King Street,
Tai Po Industrial Estate, Tai Po, N.T., Hong Kong
852-26668334

TECHNICAL INFORMATION CENTER:

1-800-521-6274

HOME PAGE:

http://www.motorola.com/semiconductors

DOCUMENT COMMENTS:

FAX (512) 933-2625,
Attn: RISC Applications Engineering

MOTOROLA



Figure 9-4. MPX Address Bus Arbitration—Non-Parked Case

9.3.1.2 MPX Address Bus Parking

External arbiters must allow only one device at a time to be the address bus master. In systems with only a single master, $\overline{BG}$ can be grounded (always asserted) to continually grant mastership of the address bus to the MPC7451. This continual granting of mastership is called bus parking.

If the MPC7451 asserts $\overline{BR}$ before the external arbiter asserts $\overline{BG}$, the MPC7451 is considered unparked, as shown in Figure 9-4. Figure 9-5 shows the parked case, where a qualified bus grant exists on the clock edge following a *need_bus* condition.



Figure 9-5. MPX Address Bus Arbitration—Parked Case

Whereas a non-parked processor must continually reassert $\overline{BR}$ to the arbiter in order to receive a bus grant, bus parking allows the arbiter to hold $\overline{BG}$ asserted. Parking permits the processor to skip the bus request (note its inactivity in Figure 9-5) and on the next cycle assume address bus ownership. Address bus tenures can be driven every other cycle by the same master.

BENEFIT OF PARKING

The overall access latency for the memory transaction is shortened by one cycle: the system gains back not only the arbitration latency, but also the dead cycle that is between each tenure in the MPX bus interface.

Typically, bus parking is provided to the device that was the most recent bus master; however, system designers may choose other schemes such as providing unrequested bus grants in situations where it is easy to predict correctly the next device requesting bus mastership.

From the system arbiter's perspective, address bus parking must be implemented more carefully in MPX bus systems than in 60x bus systems because the qualified bus grant equation no longer includes the $\overline{ABB}$ signal.

As shown in Figure 9-6, optimal address parking can be implemented in a multimaster system because $\overline{TS}$ is still in the qualified bus grant equation for MPX bus masters.



Cycle 1: Master 0 has a parked address bus grant. Master 0 has an address tenure ready and a qualified bus grant, so it queues an address tenure for the next cycle. Also in cycle 1, the arbiter samples a bus request from master 1, so the arbiter queues a switch of the bus grants from master 0 to master 1. The arbiter can safely do this because the qualified bus grant equation for MPX bus masters includes ¬TS.

Cycle 2: Master 0 begins an address tenure, and master 1 does NOT get a qualified bus grant.

Cycle 3: The arbiter MUST negate the bus grant to master 1 because, without an address bus busy indication or $\overline{AACK}$ in the qualified bus grant equation, nothing would prevent master 1 from beginning an address tenure in cycle 4 and colliding with the end of master 0's address tenure. Because it would introduce a difficult timing path to require the arbiter to sample TS in cycle 2 and negate $\overline{BG1}$ in cycle 3, it is suggested that arbiters always pulse $\overline{BGx}$ high a cycle after swapping $\overline{BGx}$ and $\overline{BGy}$, only reasserting $\overline{BGx}$ after $\overline{AACK}$ has been driven.

Cycle 4: The arbiter reasserts $\overline{BG1}$ because it asserted $\overline{AACK}$ in the previous cycle. (If the arbiter does not know in advance when $\overline{AACK}$ is to be asserted, this timing might be difficult, and the reassertion of bus grant may have to be delayed a cycle, but most systems should be able to do this.)

Cycle 5: Master 1 gets to start its address tenure. Note that this is the optimal timing for a new master to drive the address bus.

Cycles 5 and 6: The arbiter speculatively parks $\overline{BG1}$ enabling master 1 to begin another address tenure immediately in cycle 7.

Figure 9-6. Address Parking in MPX Bus Multiprocessor Systems

9.3.2 MPX Bus A

During the address transfe
transferred from the bus m

Snooping logic may monit
bus snooping in Section 9.
in this phase are transfer st
tables.

The MPC7451 supports
operated on (or *munged*) b
is performed internally be
little-endian mode is sele
That is, byte address 0 of
the most significant (left-n
swapping or other operati
MPC7451 is interfaced to

Note that the MPC7451
mode if misaligned data is

The signals used in the ad

- Address transfer st
- Address transfer si
- Address transfer at
  (TSIZ[0:2]), transf
  global (GBL)

The MPC7451 can be
HID0[XAEN]. When exte
output, the four most sig
cannot be left floating. If
by the system during the
pulldown resistor. When
a 36 bit physical address.

Figure 9-7 shows that the
address transfer and add
grouping in Figure 9-7. T
transfer and the address
synchronous bus).

In Figure 9-7, the address
in bus clock cycle 0, and
the address bus terminati